



T445529

30.5L-32 20 FOREST KING TRS LS-2 SF TL

Nokian Forest King TRS LS-2 is a forestry machine traction tyre with a strong traction bar and excellent grip. Durable special rubber compound and efficient steel fortification make it an excellent tyre for skidders.

For demanding use

Wide and efficient, Nokian Forest King TRS LS-2 has a high load-bearing capacity for today's demands. The tread pattern has been developed for even higher traction. The open-centre tread design cleans itself well.

Design features

Nokian Forest King TRS LS-2 has a very straight tread, which creates traction across the entire surface. The tyre shoulders are especially strong. Nokian Forest King TRS LS-2 also features a design that prevents wood from penetrating between tyre bead and rim flange.

-
- TYRES FOR LOG SKIDDERS, WIDE TREAD WITH HIGH TRACTION LUGS
 - SPECIAL CUT AND CRACK RESISTANT COMPOUND
 - STEEL FORTIFICATION AGAINST PUNCTURES



Technical data

[Metric](#) | [US units](#)

26"	23.1-26	Nokian Forest King TRS LS-2 30.5L-32						
	28L-26							
32"	24.5-32							
	30.5L-32	LI / SS	Rim	Permitted rims	Width	Diameter	Static loaded radius	Tread depth
	30.5L-32		32 in		795 mm	1857 mm	824 mm	
	35.5L-32	Rolling circumference	Speed radius index	Max inflation pressure		PR		
		5492 mm	-	Max. 240 kPa		20		
		Load capacity			Product code			
		10 km/h 8400 kg (240 kPa) 30 km/h 6000 kg (210 kPa)			T445529			

- **T445597** 750/55-26.5 20 NORDMAN FOREST F SF

Nokian Nordman Forest F tyre is a new type of cost-effective solution for forestry. The price and quality ratio has been optimized without compromise in terms of reliability or functionality. The strong, reliable Nokian Nordman Forest F gives you the familiar Nokian quality for less.

Tough choice

The Nokian Nordman Forest F employs a purpose-designed rubber compound that gives the tyre excellent cut and puncture resistance, even under extreme conditions. Its strong, reliable tread structure ensures high load-bearing capacity and good wear resistance. The tyre's operating hours are optimised for used machines.

Excellent replacement

The same tracks and chains are compatible with both the Nokian Forest King F and the Nokian Nordman Forest F. The recommended rims and inner tubes for the Nokian Nordman Forest F are the same as for its design basis, the Nokian Forest King F.

RELIABLE TYRE FOR DEMANDING CONDITIONS
 EXCELLENT CUT AND PUNCTURE RESISTANCE
 HIGH LOAD-BEARING CAPACITY



22.5"	710/40-22.5
24.5"	710/40-24.5
26.5"	600/55-26.5
	710/45-26.5
	750/55-26.5

Nokian Nordman Forest F
750/55-26.5

LI / SS	Rim	Permitted rims	Width	Diameter	Static loaded radius	Tread depth
177 A8 / 184 A2	26.5 in		750 mm	1485 mm	680 mm	

Rolling circumference	Speed radius index	Max inflation pressure	PR
4467 mm	-	500 kPa	20

Load capacity	Product code
10 km/h forestry service/LT 9000 kg	T445597
20 km/h road service 8980 kg	
30 km/h road service 7810 kg	
40 km/h road service 7300 kg	